



## Secure connection of **MDF boards**

**For special application on MDF boards and other thin-walled boards made of derived wood products.**

- The specially designed *CUT point* ensures exact screw positioning.
- **SPAX typical ground serrations** for quick and secure fastening.
- Effectively reduces splitting and bulging of the MDF material when turning into thin or small surfaces.
- The screw's geometry allows MDF boards and thin chipboard to be screwed together without pre-drilling (wood-dependent).
- The slender head with the ribbed underside countersinks easily into the material.



## Flat countersunk head, **T-STAR plus**

Small 75° milling head, *CUT point*, case hardened, slide-coated



A9J



Dimensions [mm]				Packaging units			SPAX-No.	EAN code
Thread Ø d1	Length total Ls	Length partial thread LgT	BIT size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty		
<b>3.5</b> Ø d <sub>k</sub> = 6.0 mm	40	28	15	200	2,000	224,000	0441010350403	4003530168437
	45	30	15	200	2,000	126,000	0441010350453	4003530168444
	50	35	15	200	2,000	126,000	0441010350503	4003530168451
<b>4.0</b> Ø d <sub>k</sub> = 7.0 mm	40	28	20	200	2,000	126,000	0441010400403	4003530168468
	45	30	20	200	2,000	126,000	0441010400453	4003530168475
	50	35	20	200	2,000	126,000	0441010400503	4003530168482
	60	40	20	100	1,000	63,000	0441010400603	4003530168499
<b>4.5</b> Ø d <sub>k</sub> = 8.0 mm	45	30	20	200	2,000	126,000	0441010450453	4003530168505
	50	35	20	200	2,000	64,000	0441010450503	4003530168512